

CLEANWELL

HIGH PRESSURE CLEANING EQUIPMENT



HS

STATIC HOT & COLD PRESSURE CLEANERS

- ✓ Long life, slow revving, industrial 1400 RPM electric motor coupled to a brass headed Interpump pump
- ✓ Improved high efficiency burner which is able to produce up to 150°C through a steam valve system
- ✓ Supplied with 9m high pressure hose, on/off gun, lance & nozzle
- ✓ The polyethylene water tank also meets Water Bylaws regulations
- ✓ Designed and manufactured by Cleanwell to comply with CE Legislation
- ✓ 1 Year warranty subject to conditions of sale

- ✓ Performances ranging from 50 bar to 350 bar in 110v, 240v and 415v. Available as oil fired or electrically heated
- ✓ Fitted as standard with 24 volt control, anti leak detection and auto time delayed shut down at zero pressure which has proven to reduce maintenance costs by 75%
- ✓ To prolong the life of the chassis it is constructed of zintec coated steel with a polyester finish. Also available in stainless steel



British Manufacturer

let Cleanwell handle the pressure

HS OIL FIRED HOT HIGH PRESSURE CLEANERS

PERFORMANCE SPECIFICATIONS

OPERATING PRESSURE		FLOW RATE	VOLTAGE	MOTOR
PSI	BAR	LITRES PER MINUTE		
1500	100	12	110V	3.0 HP
1500	100	12	240V	3.4 HP
1500	100	14	240V	3.4 HP
2200	150	14	415V	5.5 HP
2200	150	21	415V	7.5 HP
2500	175	18	415V	7.5 HP
3000	200	15	415V	7.5 HP

PUMP	3 PISTON PLUNGER INTERPUMP	MAXIMUM INLET TEMP.	40°C
MOTOR	INDUSTRIAL SLOW REVING	OUTLET TEMP RANGE	10-150°C
AUTO TIME STOP	ADJUSTABLE	WATER TANK	21 LTR
VOLTAGE CONTROLS	24 VOLTS		
DIMENSIONS	H – 1620 MM	W – 940 MM	L – 550 MM

OPTIONS

ALL STAINLESS STEEL	FROST PROTECTION	DIESEL TANK WITH FLOAT SWITCH
CHEMICAL SOLENOID	REMOTE CONTROL	TIMED CHEMICAL OPERATION
LOCKABLE CONTROL PANEL	KEY ISOLATOR	RCD ELCB
COIN OR TOKEN OPERATION WITH TIMED CYCLES	RETRACTABLE/MANUAL HOSEREEL	INTERNAL CHEMICAL & FUEL SUPPLY
LOW PRESSURE CHEMICAL BURNER FLAME FAILURE	1000 LTR BUNDED FUEL TANK	SPRUNG LOADED BOOMS
	TWO MAN OPERATION	WATER SOFTENER