

# CLEANWELL

## HIGH PRESSURE CLEANING EQUIPMENT

# SS

### HOT HIGH PRESSURE CLEANER



- ✔ Fitted as standard with 24 volt control, anti leak detection and auto time delayed shut down at zero pressure which maintains the life of the machine and protects the operator
- ✔ The automatic time delayed shut down has proven to reduce maintenance costs by 75%
- ✔ The fuel tank comes complete with triple fuel filter system, low level fuel cut out & instant self bleeding system which is controlled by an electronic fuel pump
- ✔ Supplied with 30ft. high pressure hose, on/off gun, lance & nozzle
- ✔ Long life, slow revving 1400 RPM electric motor direct coupled to an Interpump pump which is able to suck from an outside water tank
- ✔ Performances ranging from 1500 psi 100 bar to 3000 psi 200 bar. Available in all electrical supplies 110v, 240v, 415v. Also available as an electrically heated high pressure
- ✔ The 4 wheeled stove enamelled chassis comes complete with a long life, weather resistant, rust-proof stainless steel cover fitted with a stainless steel water tank which meets the Water Bylaws regulations
- ✔ High pressure chemical injection complete with metering valve
- ✔ Improved high efficiency burner which is able to produce up to 150°C through a steam valve system
- ✔ Environmentally friendly specification
- ✔ Designed and manufactured by Cleanwell to comply with CE Legislation
- ✔ 1 Year guarantee subject to conditions of sale

British Manufacturer

## let Cleanwell handle the pressure

# SS OIL FIRED HOT HIGH PRESSURE CLEANERS

## PERFORMANCE SPECIFICATIONS

OPERATING PRESSURE		FLOW RATE	VOLTAGE	MOTOR
PSI	BAR	LITRES PER MINUTE		
1500	100	12	240V	3.4 HP
1500	100	14	240V	3.4 HP
1500	100	12	110V	3.0 HP
2200	150	14	415V	5.5 HP
2200	150	21	415V	7.5 HP
2500	175	18	415V	7.5 HP
3000	200	15	415V	7.5 HP

<b>PUMP</b>	3 PISTON PLUNGER INTERPUMP	<b>DIESEL FUEL TANK</b>	23 LTR
<b>MOTOR</b>	BROOK HANSEN	<b>WATER TANK</b>	21 LTR
<b>AUTO TIME STOP</b>	ADJUSTABLE	<b>MAXIMUM INLET TEMP.</b>	40°C
<b>VOLTAGE CONTROLS</b>	24 VOLTS	<b>OUTLET TEMP RANGE</b>	10-150°C
<b>DIMENSIONS</b>	H – 760mm 30"	W – 740mm 29"	L – 1040m 41"

## OPTIONS

LOW PRESSURE CHEMICAL	CHEMICAL SOLENOID	RCD
REMOTE CONTROL	WATER SOFTENER	HOSE REELS
LONGER LANCE	TWIN LANCE	FOAM LANCE
FLOOR CLEANER	ROTARY BRUSH	SAND BLASTING KIT
TURBO NOZZLE	DRAIN CLEANING NOZZLE	ROTARY NOZZLE