CLEANING EQUIPMENT

MMH

HOT PRESSURE CLEANERS

Also available in a Cold Water version

Performances ranging from 1500 psi 100 bar to 3000 psi 200 bar in 110v, 240v, 415v

CLEANW

This is built as cold water wall mounted machine and comes with its own wall mounting kit

It's also available with the facility to supply it with hot water up to 85 degrees centigrade on selected models

Fitted as standard with 24 volt control, anti leak detection and auto time delayed shut down at zero pressure which has proven to reduce maintance costs by 75% To prolong the life of the chassis it is constructed of steel which is zintec coated with a polyester finish with a stainless steel cover. Also available in all Stainless Steel

- Long life, slow revving, industrial 1400 RPM electric motor coupled to a brass headed Interpump pump
- Supplied with 9m high pressure hose, on/off gun, lance & nozzle
 - Designed and manufactured by Cleanwell to comply with CE Legislation
 - 1 Year warranty subject to conditions of sale

British Manufacturer

let Cleanwell handle the pressure

WALL MOUNT HOT WATER PRESSURE CLEANERS				
Operating Pressure	Flow Rate	Voltage	Motor	
(Able to accept water up to 85°C)				

PERFORMANCE SPECIFICATIONS					
PSI	Bar	Litres Per Minute	Voltage	Motor	
1500	100	13	240v	3.4 HP	
2320	160	13	415v	5.5 HP	
2610	180	15	415v	7.5 HP	

SPECIFICATIONS

Pump	3 Piston Plunger Interpump	Maximum Inlet Temp.	50°C
Motor	Slow Revving Industrial Motor 2 Motor Bearing	Chemical System	Low Pressure Chemical Injection
Auto Time Stop	Adjustable – Factory Set 2 minutes	Electric Cable	240v 30ft/9m 415v 20ft/6m
Low Voltage Controls	24 volts 240v	Weight	70kg
Dimensions	Height 385mm	Width 750mm	Depth 830mm

OPTIONS				
5 ltr Water break tank	Frost Protection	Remote Control		
Key Isolator	Water Softener	Start/Stop from Gun		
Sprung Loaded Booms (In stainless steel)	High Pressure Chemical Injection	Coin Mec Box (For token operation)		